

Open Geospatial Consortium

Publication Date: 2016-11-02

Approval Date: 2016-04-11

Submission Date: 2015-07-01

External identifier of this OGC® document: <<http://www.opengis.net/doc/BP/gmlcov/1.0/jpip-jp2000/1.0>>

Normative version: <http://docs.opengeospatial.org/bp/14-110r2/14-110r2.html>

Reference number of this document: OGC 14-110r1r2

Category: OGC® Best Practice

Editor: Dimitri Sarafinof

OGC® GML Application Schema - Coverages JPEG2000/JPIP Coverage Encoding Extension

Copyright © 2015,2016 Open Geospatial Consortium.

To obtain additional rights of use, visit <http://www.opengeospatial.org/legal/>.

Warning

This document defines an OGC Best Practice on a particular technology or approach related to an OGC standard. This document is not an OGC Standard and may not be referred to as an OGC Standard. It is subject to change without notice. However, this document is an official position of the OGC membership on this particular technology topic.

Document type:	OGC® Best Practice
Document subtype:	Encoding
Document stage:	Approved
Document language:	English

License Agreement

Permission is hereby granted by the Open Geospatial Consortium, ("Licensor"), free of charge and subject to the terms set forth below, to any person obtaining a copy of this Intellectual Property and any associated documentation, to deal in the Intellectual Property without restriction (except as set forth below), including without limitation the rights to implement, use, copy, modify, merge, publish, distribute, and/or sublicense copies of the Intellectual Property, and to permit persons to whom the Intellectual Property is furnished to do so, provided that all copyright notices on the intellectual property are retained intact and that each person to whom the Intellectual Property is furnished agrees to the terms of this Agreement.

If you modify the Intellectual Property, all copies of the modified Intellectual Property must include, in addition to the above copyright notice, a notice that the Intellectual Property includes modifications that have not been approved or adopted by LICENSOR.

THIS LICENSE IS A COPYRIGHT LICENSE ONLY, AND DOES NOT CONVEY ANY RIGHTS UNDER ANY PATENTS THAT MAY BE IN FORCE ANYWHERE IN THE WORLD.

THE INTELLECTUAL PROPERTY IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS NOTICE DO NOT WARRANT THAT THE FUNCTIONS CONTAINED IN THE INTELLECTUAL PROPERTY WILL MEET YOUR REQUIREMENTS OR THAT THE OPERATION OF THE INTELLECTUAL PROPERTY WILL BE UNINTERRUPTED OR ERROR FREE. ANY USE OF THE INTELLECTUAL PROPERTY SHALL BE MADE ENTIRELY AT THE USER'S OWN RISK. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR ANY CONTRIBUTOR OF INTELLECTUAL PROPERTY RIGHTS TO THE INTELLECTUAL PROPERTY BE LIABLE FOR ANY CLAIM, OR ANY DIRECT, SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM ANY ALLEGED INFRINGEMENT OR ANY LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR UNDER ANY OTHER LEGAL THEORY, ARISING OUT OF OR IN CONNECTION WITH THE IMPLEMENTATION, USE, COMMERCIALIZATION OR PERFORMANCE OF THIS INTELLECTUAL PROPERTY.

This license is effective until terminated. You may terminate it at any time by destroying the Intellectual Property together with all copies in any form. The license will also terminate if you fail to comply with any term or condition of this Agreement. Except as provided in the following sentence, no such termination of this license shall require the termination of any third party end-user sublicense to the Intellectual Property which is in force as of the date of notice of such termination. In addition, should the Intellectual Property, or the operation of the Intellectual Property, infringe, or in LICENSOR's sole opinion be likely to infringe, any patent, copyright, trademark or other right of a third party, you agree that LICENSOR, in its sole discretion, may terminate this license without any compensation or liability to you, your licensees or any other party. You agree upon termination of any kind to destroy or cause to be destroyed the Intellectual Property together with all copies in any form, whether held by you or by any third party.

Except as contained in this notice, the name of LICENSOR or of any other holder of a copyright in all or part of the Intellectual Property shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Intellectual Property without prior written authorization of LICENSOR or such copyright holder. LICENSOR is and shall at all times be the sole entity that may authorize you or any third party to use certification marks, trademarks or other special designations to indicate compliance with any LICENSOR standards or specifications. This Agreement is governed by the laws of the Commonwealth of Massachusetts. The application to this Agreement of the United Nations Convention on Contracts for the International Sale of Goods is hereby expressly excluded. In the event any provision of this Agreement shall be deemed unenforceable, void or invalid, such provision shall be modified so as to make it valid and enforceable, and as so modified the entire Agreement shall remain in full force and effect. No decision, action or inaction by LICENSOR shall be construed to be a waiver of any rights or remedies available to it.

Contents	Page
1. Scope.....	7
2. Conformance.....	7
3. Normative references	7
4. Terms and Definitions.....	8
5. Overview and conventions.....	8
5.1 Overview (informal).....	8
5.2 Namespace prefix conventions.....	9
5.3 Multiple representations	9
6. JPEG2000 coverage requirements class	9
6.1 GetCapabilities	9
6.2 DescribeCoverage.....	10
6.3 GetCoverage	10
6.3.1 GetCoverage request.....	10
6.3.2 GetCoverage response.....	13
6.3.3 GetCoverage exceptions	14
6.4 Examples.....	15
7. JPIP access requirements class	16
7.1 GetCapabilities	16
7.2 DescribeCoverage.....	17
7.3 GetCoverage	17
7.3.1 GetCoverage request.....	17
7.3.2 GetCoverage response.....	18
7.3.3 GetCoverage exceptions	19
Annex A: Conformance Class Abstract Test Suite (Normative).....	20
A.1 Conformance class: jpeg2000-coverage.....	20
A.1.1 Prerequisites.....	20
A.1.2 Include GMLCOV extension identifier	20
A.1.3 Include WCS extension identifier	20
A.1.4 Include format supported	21
A.1.5 Native format	21
A.1.6 Format parameter	22
A.1.7 Additional parameters	22
A.1.8 Format returned.....	22
A.1.9 Parameter for profile	23
A.1.10 Parameter for compression.....	24
A.1.11 Parameter for tiling	24
A.1.12 Parameter for georeference	25
A.1.13 Exceptions.....	25

A.2	Conformance Test Class: <i>jpip-access</i>	25
A.2.1	Prerequisites.....	26
A.2.2	Include GMLCOV extension identifier.....	26
A.2.3	Include Service extension identifier.....	26
A.2.4	Include format supported.....	26
A.2.5	Native format.....	27
A.2.6	Format parameter.....	27
A.2.7	Additional parameters.....	28
A.2.8	Format returned.....	28
A.2.9	Parameter for profile.....	29
A.2.10	Parameter for compression.....	29
A.2.11	Parameter for tiling.....	30
A.2.12	Parameter for georeference.....	30
A.2.13	Exceptions.....	31
Annex B:	Revision history.....	32

Tables	Page
Table 1 – Namespace mappings.....	9
Table 2 – GetCoverage additional parameters for JPEG2000 encoding.....	11
Table 3 – Exception codes for JPEG2000.....	14

i. Abstract

Coverages represent space/time-varying phenomena, such as satellite imagery, digital elevation models, or digital aerial imagery. OGC Abstract Topic 6 [OGC 07-011] – which is identical to ISO 19123 – defines an abstract model of coverages. Coverage instances may be encoded using the GML Application Schema – Coverages – JPEG2000 Coverage Encoding Extension version 1.0 [OGC 12-108] which is based on the GML Application Schema – Coverages (GMLCOV) version 1.0 [OGC 09-146r2] which in turn is based on the Geography Markup Language (GML) version 3.2 [07-036], an XML grammar written in XML Schema for the description of application schemas as well as the transport and storage of geographic information.

This extension to the Web Coverage Service (WCS) 2.0 Interface Standard – Core (WCS) version 2.0 [OC 09-110r4] specifies the usage of the JPEG2000 coverage encoding and JPIP streaming capabilities with WCS. The approach is based on the authoritative GML Application Schema – Coverages – JPEG2000 Coverage Encoding Extension version 1.0 [OGC 12-108].

ii. Keywords

Ogdoc, ogc documents, wcs, jpeg2000, jpip, extension

iii. Preface

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. The Open Geospatial Consortium shall not be held responsible for identifying any or all such patent rights.

Recipients of this document are requested to submit, with their comments, notification of any relevant patent claims or other intellectual property rights of which they may be aware that might be infringed by any implementation of the standard set forth in this document, and to provide supporting documentation.

iv. Submitting organizations

The following organizations submitted this Document to the Open Geospatial Consortium (OGC):

- IGN France
- Strobel Geoinformatics

v. Submitters

All questions regarding this document should be directed to the editor or the contributors:

Name	Organization
Dimitri Sarafinof	IGN, France
Stefan Strobel	Strobel Geoinformatics

1. Scope

This OGC® *Web Coverage Service 2.0 Candidate Interface Standard – JPEG2000/JPIP Coverage Encoding Extension* – henceforth abbreviated as “JPEG2000-Coverages” specifies the usage of JPEG2000 coverage encoding retrieval through a JPIP URL with WCS.

2. Conformance

This document establishes the following requirements and conformance class:

- *jpeg2000-access* of URI http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/req/jpeg2000-access, with a single pertaining conformance class, *jpeg2000-access*, of URI http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpeg2000-access.
- *jpeg2000-jpip-access* of URI http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/req/jpeg2000-jpip-access, with a single pertaining conformance class, *jpeg2000-jpip-access*, of URI http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpeg2000-jpip-access.

Standardization target of all conformance classes are concrete coverage instance documents, as generated by some service and/or consumed by some client.

Note: a concrete coverage instance can be a GMLCOV instance document with a reference to a specific file (for example through a JPIP URL).

URIs given in this document for each requirement or conformance test URIs are relative paths to be appended to the root http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/.

Annex A lists the conformance tests which shall be exercised on any software artifact claiming to implement *jpeg2000-access* and/or *jpeg2000-jpip-access* conformance classes.

3. Normative references

This JPEG2000/JPIP-Coverages Best Practice consists of this document and an associated XML Schema. The complete Best Practice is identified by the OGC URI:

http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0,

the document has an OGC URI:

http://www.opengis.net/doc/ISx/GMLCOV_jpeg2000-coverages/1.0.

The complete WCS standard is available for download from <http://www.opengeospatial.org/standards/wcs>; additionally, the XML Schema is posted online at <http://bp.schemas.opengis.net/14-110r2/gmlcov/jpeg2000/1.0> as part of the OGC schema repository. In the event of a discrepancy between bundled and schema

repository versions of the XML Schema files, the schema repository shall be considered normative.

The following normative documents contain provisions that, through reference in this text, constitute provisions of this candidate standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. For undated references, the latest edition of the normative document referred to applies.

[1] OGC 12-108, *OGC® GML Application Schema - Coverages – JPEG2000 Coverage Encoding Extension*, version 1.0

Conformance classes used:

- jpeg2000-coverage

[2] OGC 09-110r4, *OGC® Web Coverage Service 2.0 Interface Standard – Core*, version 2.0

Conformance classes used:

- core

[3] ISO/IEC 15444-1, *Information technology — JPEG2000 Image Coding System. Part 1: Core coding system*

[4] ISO/IEC 15444-2, *Information technology — JPEG2000 Image Coding System: Part 2: Extensions*

[5] IETF RFC3745 *MIME Type Registrations for JPEG 2000 (ISO/IEC 15444)*

4. Terms and Definitions

This document uses the terms defined in Sub-clause 5.3 of [OGC 06-121r8], which is based on the ISO/IEC Directives, Part 2, Rules for the structure and drafting of International Standards. In particular, the word “shall” (not “must”) is the verb form used to indicate a requirement to be strictly followed to conform to this standard.

For the purposes of this document, the terms and definitions given in the above references apply.

5. Overview and conventions

5.1 Overview (informal)

JPEG 2000¹ (JP2) is an image compression standard and coding system. It was created by the Joint Photographic Experts Group committee in **2000** with the intention of superseding their original discrete cosine transform-based **JPEG** standard (created in 1992) with a newly designed, wavelet-based method. Please find further details in the

¹ http://en.wikipedia.org/wiki/JPEG_2000

OGC® GML Application Schema - Coverages – JPEG2000 Coverage Encoding Extension [OGC 12-108].

5.2 Namespace prefix conventions

The following namespaces are used in this document. The prefix abbreviations used constitute conventions used here, but are **not** normative. The namespaces to which the prefixes refer are normative, however.

Table 1 – Namespace mappings

Prefix	Namespace URI	Description
xsd	http://www.w3.org/2001/XMLSchema	XML Schema namespace
gml	http://www.opengis.net/gml/3.2	GML 3.2.1
gmlcov	http://www.opengis.net/gmlcov/1.0	GML Application Schema – Coverages 1.0
wcs	http://www.opengis.net/wcs/2.0	WCS 2.0
jpeg2000	http://www.opengis.net/gmlcov/jpeg2000/1.0	JPEG2000-Coverages 1.0

5.3 Multiple representations

Where representations of the same information are given in this OGC Best Practice and the associated XML schema document and there are differences in the representations, the XML schema shall take precedence.

6. JPEG2000 coverage requirements class

Requirements class *jpeg2000-access* establishes how JPEG2000 encoded coverages can be requested from a WCS including parameters defining JPEG2000 features like compression, tiling, etc. Its identifying URL is given by http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/req/jpeg2000-access.

6.1 GetCapabilities

The support of JPEG2000 coverage encoding shall be advertised in `ows:Profile` and a `wcs:formatSupported` elements.

Requirement 1 /req/jpeg2000-coverage/gmlcov-extension-identifier:

A WCS implementing this extension **shall** include the following URI in a `ows:Profile` element of the `ows:ServiceIdentification` in a *GetCapabilities* response:

http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpeg2000-coverage.

Dependency: http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpeg2000-coverage

Requirement 2 /req/jpeg2000-coverage/service-extension-identifier:

A WCS implementing this extension **shall** include the following URI in a `ows:Profile` element of the `ows:ServiceIdentification` in a *GetCapabilities* response:

http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpeg2000-access.

Requirement 3 /req/jpeg2000-coverage/format-supported:

A WCS implementing this extension **shall** include the following MIME type identifier in a `wcs:formatSupported` element in the `wcs:ServiceMetadata` element in a *GetCapabilities* response:

`image/jp2` and/or `image/jpx`

according to compliance to ISO 15444-1 or ISO 15444-2

Dependency: http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpeg2000-coverage

6.2 DescribeCoverage

Requirement 4 /req/jpeg2000-coverage/native-format:

A coverage served via WCS and native format JPEG2000 **shall** use the following MIME type identifier in the `wcs:nativeFormat` element in the `wcs:ServiceParameters` element in a *DescribeCoverage* response:

`image/jp2` or `image/jpx`

according to compliance of JPEG2000 files available on the server to ISO 15444-1 or ISO 15444-2

Dependency: http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpeg2000-coverage

6.3 GetCoverage

6.3.1 GetCoverage request

Requirement 5 /req/jpeg2000-coverage/format-requested:

In a *GetCoverage* request requesting a coverage in JPEG2000 encoding the `format` parameter value **shall** be the following MIME type identifier:

`image/jp2` or `image/jpx`

Dependency: http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpeg2000-coverage

The following additional *parameters* are defined for requesting JPEG2000 encoded coverages via *GetCoverage* requests.

Note: It is always possible for a given coverage instance to determine its current parameter values, i.e., the parameter values used at creation. Thus a JPEG2000 encoded coverage is self-describing.

Requirement 6 /req/jpeg2000-coverage/additional-parameters:
 The structure of a *GetCoverage* request requesting a coverage in JPEG2000 encoding **shall** be extended as defined in Table 2 and the respective XML Schema being part of this standard.

Note: In case of using KVP protocol binding, it is recommended for server implementations to parse the format parameter first in order to have the right context for further parameters.

Table 2 – GetCoverage additional parameters for JPEG2000 encoding

Name	Definition	Data Type	Multiplicity
profile	JPEG2000 profile used	String, one of: "PROFILE0", "PROFILE1", "PROFILE2"	zero or one (optional)
compression	JPEG2000 compression rates and quality layers. Only the smallest compression rate defines the size of the data. The other rates define quality layers available.	String with coma separated list of compression rates "10,20,50" "- "shall be used for lossless compression	zero or one (optional)
tiling	Indicates if tiling is requested. If tiling is requested, then both tileheight and tilewidth shall be provided. No tiling implies one tile which size is the coverage size.	Boolean	zero or one (optional)

tileheight	Tile height in pixels; allowed only together with tiling being "true" and tilewidth being present No tile parameter implies tile size being the maximum allowed by the profile (if specified).	Integer greater than zero	zero or one (conditional to tiling="true")
tilewidth	Tile width in pixels; allowed only together with tiling being "true" and tileheight being present	Integer greater than zero	zero or one (conditional to tiling="true")
precinct	Indicates if precinct is requested. If precinct is requested, then precinctsize shall be provided.	Boolean	zero or one (optional)
precinctsize	Precinct dimensions (must be powers of 2). Multiple records may be supplied, in which case the first record refers to the highest resolution level and subsequent records to lower resolution levels. The last specified record is used for any remaining lower resolution levels. Inside each record, vertical coordinates appear first.	String with comma separated list of records i.e {256,256},{128,128},{64,64}	zero or one (conditional to precinct="true")

georeference	Specifies how the georeference is provided. It can follow GeoJP2 specification or GMLJP2 OGC Standard. GMLJP2 requires format="image/jpx"	String, one of: "GEO", "GML", "GEO_GML"	zero or one
--------------	---	---	-------------

NOTE: depending of the profile used, restrictions may apply on others parameters (tiles size ...).

6.3.2 GetCoverage response

A JPEG2000 encoded coverage follows the OGC® GML Application Schema - Coverages – JPEG2000 Coverage Encoding Extension [OGC 12-108] and thus the JPEG2000 format Specifications ([3] and [4]).

Requirement 7 /req/jpeg2000-coverage/format-returned:

The response to a successful *GetCoverage* request containing a `format` parameter with value `image/jp2` or `image/jpx` **shall** consist of a coverage encoded as specified in the OGC® GML Application Schema - Coverages – JPEG2000 Coverage Encoding Extension [OGC 12-108].

Dependency: http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpeg2000-coverage

A JPEG2000 encoded coverage encodes the JPEG2000 features as requested in a *GetCoverage* request.

Requirement 8 /req/jeg2000-coverage/profile:

The response to a successful *GetCoverage* request containing a `profile` parameter **shall** consist of a JPEG2000 encoded coverage according to JPEG2000 format Specifications ([3] and [4]).

Requirement 9 /req/jpeg2000-coverage/compression:

The response to a successful *GetCoverage* request containing a `compression` parameter shall consist of a JPEG2000 encoded coverage using the specified compression rates.

Requirement 10 /req/jpeg2000-coverage/tiling:

The response to a successful *GetCoverage* request containing a `tiling` and a `tileheight` and a `tilewidth` parameter **shall** consist of a JPEG2000 encoded coverage with internal tiling using the specified height and width.

Requirement 11 /req/jpeg2000-coverage/georeference:

The response to a successful *GetCoverage* request containing a georeference parameter **shall** consist of a JPEG2000 encoded coverage with georeference information included.

Note: A server not implementing the requested feature is always free to respond with an exception.

6.3.3 GetCoverage exceptions**Requirement 12 /req/jpeg2000-coverage/exceptions:**

When a WCS server encounters an error described in column “meaning of exception code” in Table 3 then it **shall** return the corresponding exception report message with the contents of the locator parameter value as specified in the right column of Table 3.

Dependency: <http://www.opengis.net/spec/WCS/2.0/conf/core>

Table 3 – Exception codes for JPEG2000

exceptionCode value	HTTP code	Meaning of code	locator value
ProfileNotSupported	404	Server does not support the requested profile.	Value of profile parameter.
ProfileInvalid	404	Invalid profile requested.	Value of profile parameter.
CompressionNotSupported	404	Server does not support the requested compression.	Value of compression parameter.
CompressionInvalid	404	Invalid compression requested.	Value of compression parameter.
TilingNotSupported	404	Server does not support tiling.	–
TilingInvalid	404	Either tileheight, tilewidth, or both are missing or one or both are not a positive integer and thus invalid.	Value of tileheight and tilewidth parameter.
GeoreferenceNotSupported	404	Server does not support the requested georeference.	Value of georeference parameter.

GeoreferenceInvalid	404	Invalid georeference requested.	Value of georeference parameter.
---------------------	-----	---------------------------------	----------------------------------

6.4 Examples

Following GetCoverage request will return coverage with id Coverage1 in JPEG2000 with GeoJP2 georeference.

Get/KVP encoding

<http://www.myserver.com/wcs?service=WCS &version=2.0.1 &request=GetCoverage&coverageId=Coverage1&format=image/jp2 &profile=PROFILE1&compression=10,20,50&tiling=true&tileheight=1024&tilewidth=1024&precinct=yes&precinctSize={256,256},{128,128},{64,64}&georeferenced=GEO>

XML/POST encoding

```
<?xml version="1.0" encoding="UTF-8"?>
<GetCoverage xmlns="http://www.opengis.net/wcs/2.0" service="WCS" version="2.0.1"
xmlns:jpeg2000="http://www.opengis.net/gmlcov/jpeg2000/1.0"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xsi:schemaLocation="
http://www.opengis.net/wcs/2.0 http://schemas.opengis.net/wcs/2.0/wcsGetCoverage.xsd
http://www.opengis.net/gmlcov/jpeg2000/1.0 gmlcovJPEG2000.xsd">
  <Extension>
    <jpeg2000:parameters>
      <jpeg2000:profile>PROFILE1</jpeg2000:profile>
      <jpeg2000:compression>10,20,50</jpeg2000:compression>
      <jpeg2000:tiling>true</jpeg2000:tiling>
      <jpeg2000:tileheight>1024</jpeg2000:tileheight>
      <jpeg2000:tilewidth>1024</jpeg2000:tilewidth>
      <jpeg2000:precinct>true</jpeg2000:precinct>
      <jpeg2000:precinctsize>{256,256},{128,128},{64,64}</jpeg2000:precinctsize>
      <jpeg2000:georeference>GEO</jpeg2000:georeference>
    </jpeg2000:parameters>
  </Extension>
  <CoverageId>Coverage1</CoverageId>
  <format>image/jp2</format>
  <mediaType>multipart/mixed</mediaType>
</GetCoverage>
```

Following example to request a coverage through a JPIP url within a multipart file:

Get/KVP encoding

<http://www.myserver.com/wcs?service=WCS &version=2.0.1 &request=GetCoverage&coverageId=Coverage1 &format=text/xml;urn:ogc:def:wcs:2.0:jpip-response&mediaType=multipart/mixed&profile=PROFILE1&compression=->

[,10,20,50&precinct=yes&precinctSize={256,256},{128,128},{64,64}&georeferenced=GEO](#)

XML/POST encoding

```
<?xml version="1.0" encoding="UTF-8"?>
<GetCoverage xmlns="http://www.opengis.net/wcs/2.0" service="WCS" version="2.0.1"
xmlns:jpeg2000="http://www.opengis.net/gmlcov/jpeg2000/1.0"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xsi:schemaLocation="
http://www.opengis.net/wcs/2.0 http://schemas.opengis.net/wcs/2.0/wcsGetCoverage.xsd
http://www.opengis.net/gmlcov/jpeg2000/1.0 gmlcovJPEG2000.xsd">
  <Extension>
    <jpeg2000:parameters>
      <jpeg2000:profile>PROFILE1</jpeg2000:profile>
      <jpeg2000:compression>10,20,50</jpeg2000:compression>
      <jpeg2000:tiling>>false</jpeg2000:tiling>
      <jpeg2000:precinct>>true</jpeg2000:precinct>
      <jpeg2000:precinctsize>{256,256},{128,128},{64,64}</jpeg2000:precinctsize>
      <jpeg2000:georeference>GEO</jpeg2000:georeference>
    </jpeg2000:parameters>
  </Extension>
  <CoverageId>Coverage1</CoverageId>
  <format>text/xml;urn:ogc:def:wcs:2.0:jpip-response</format>
  <mediaType>multipart/mixed</mediaType>
</GetCoverage>
```

7. JPIP access requirements class

Requirements class *jpip-access* establishes how JPEG2000 encoded coverages can be requested from a service and retrieved through a JPIP URL, including parameters defining JPEG2000 features like compression, tiling, etc. Its identifying URL is given by http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/req/jpip-access.

7.1 GetCapabilities

The support of JPEG2000 coverage encoding shall be advertised in `ows:Profile` and a `wcs:formatSupported` elements.

Requirement 13 /req/jpip-access/gmlcov-extension-identifier:

A WCS implementing this extension **shall** include the following URI in a `ows:Profile` element of the `ows:ServiceIdentification` in a *GetCapabilities* response:

http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpeg2000-coverage.

Dependency: http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpeg2000-coverage

Requirement 14 /req/jpip-access/service-extension-identifier:

A WCS implementing this extension **shall** include the following URI in a `ows:Profile` element of the `ows:ServiceIdentification` in a *GetCapabilities* response:

http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpip-access.

Requirement 15 /req/jpip-access/format-supported:

A WCS implementing this extension **shall** include the following MIME type identifier in a `wcs:formatSupported` element in the `wcs:ServiceMetadata` element in a *GetCapabilities* response:

`text/xml;urn:ogc:def:wcs:2.0:jpip-response`

Dependency: none

7.2 DescribeCoverage

Requirement 16 /req/jpip-access/native-format:

A coverage served via WCS and native format JPEG2000 **shall** use the following MIME type identifier in the `wcs:nativeFormat` element in the `wcs:ServiceParameters` element in a *DescribeCoverage* response:

`image/jp2` or `image/jpx`

Dependency: http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpeg2000-coverage

Note: JPIP being a protocol and not a format, the native format is reported as a JPEG2000.

7.3 GetCoverage

7.3.1 GetCoverage request

A JPEG2000 coverage that has to be streamed through a JPIP URL can only be provided with a multipart/mixed document with a reference to this URL.

Requirement 17 /req/jpip-access/format-requested:

In a *GetCoverage* request requesting a JPEG2000 coverage through a JPIP URL, the `format` parameter value **shall** be the following MIME type identifier:

`text/xml;urn:ogc:def:wcs:2.0:jpip-response`

Dependency: none

Requirement 18 /req/jpip-access/mediatype-requested:

In a *GetCoverage* request requesting a JPEG2000 coverage through a JPIP URL, the `mediatype` parameter value **shall** be the following value:

`multipart/mixed`

Dependency: http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpeg2000-coverage

The following additional *parameters* are defined for requesting JPEG2000 encoded coverages via *GetCoverage* requests.

Note: It is always possible for a given coverage instance to determine its current parameter values, i.e., the parameter values used at creation. Thus a JPEG2000 encoded coverage is self-describing.

Requirement 19 /req/jpip-access/additional-parameters:

The structure of a *GetCoverage* request requesting a coverage in JPEG2000 encoding **shall** be extended as defined in Table 2 and the respective XML Schema being part of this standard.

Note: In case of using KVP protocol binding, it is recommended for server implementations to parse the format parameter first in order to have the right context for further parameters.

Requirement 20 /req/jpeg2000-coverage/additional-parameters-constraints:

The parameters values of a *GetCoverage* request requesting a coverage in JPEG2000 encoding **shall** be compliant to restrictions defined by ISO 15444 Standard, depending on profile choice.

7.3.2 GetCoverage response

The JPIP accessed coverage follows the OGC® GML Application Schema - Coverages – JPEG2000 Coverage Encoding Extension [OGC 12-108] and thus the JPEG2000 format Specifications ([3] and [4]).

A GMLCOV JPEG2000 coverage is not different from a GMLCOV coverage with JPIP access; instead of providing a multipart document with the GML file and the JPEG2000 file, only the GML file is provided to the client.

The JPIP URL provide to the link to stream the JPEG2000 file. It means the "<gml:File>/<gml:fileReference>" element provides a JPIP URL (like <http://myserver.com/coverages/coverage1.jp2>) instead of just the file name (coverage1.jp2).

Requirement 21 /req/jpip-access/document-returned:

The response to a successful *GetCoverage* request containing a format parameter with value `text/xml;urn:ogc:def:wcs:2.0:jpip-response` and a mediatype parameter with value `multipart/mixed` **shall** be a document compliant to multipart conformance class from GMLCOV 1.0.

Dependency: <http://www.opengis.net/spec/GMLCOV/1.0/conf/multipart>

Requirement 22 /req/jpip-access/range-set:

Within the multipart document, the range set of the coverage **shall** be provided by reference (<gml:File>/<gml:fileReference>) containing the JPIP URL. The element <gml:fileStructure> **shall** have value image/jpx or image/jpeg.

The element <gml:mimeType> **shall** have value image/jpx or image/jpeg.

Dependency: <http://www.opengis.net/spec/GMLCOV/1.0/conf/multipart>

A JPEG2000 encoded coverage retrieved through a JPIP URL encodes the JPEG2000 features as requested in a GetCoverage request.

Requirement 23 /req/jpip-access/parameters:

The JPEG2000 file retrieved from the JPIP URL in a response to a successful *GetCoverage* request **shall** satisfy requirements Requirement 7, Requirement 8, Requirement 9, Requirement 10 and Requirement 11.

Note: A server not implementing the requested feature is always free to respond with an exception.

7.3.3 GetCoverage exceptions

Requirement 24 /req/jpip-access/exceptions:

When a WCS server encounters an error described in column “meaning of exception code” in Table 3 – Exception codes for JPEG2000 then it **shall** return the corresponding exception report message with the contents of the locator parameter value as specified in the right column of Table 3.

Dependency: <http://www.opengis.net/spec/WCS/2.0/conf/core>

Annex A: Conformance Class Abstract Test Suite (Normative)

This Annex specifies an Abstract Test Suite which shall be passed in completeness by any implementation claiming conformance with this JPEG2000/JPIP coverage encoding extension.

Test identifiers below are relative to

http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/

A.1 Conformance class: jpeg2000-coverage

The OGC URI identifier of this conformance class is:

http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpeg2000-access.

A.1.1 Prerequisites

Make sure that at least one coverage with JPEG2000 as native format is available from server under test.

A.1.2 Include GMLCOV extension identifier

Test id: `/req/jpeg2000-coverage/gmlcov-extension-identifier`

Test Purpose: `/req/jpeg2000-coverage/gmlcov-extension-identifier:`
 A WCS implementing this extension **shall** include the following URI in a `ows:Profile` element of the `ows:ServiceIdentification` in a *GetCapabilities* response:
http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpeg2000-coverage.
Dependency: http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpeg2000-coverage

Test method: Send a *GetCapabilities* request to the server under test and verify that the response contains a `Profile` element with said URI.

Test passes if constraint evaluates to true.

A.1.3 Include WCS extension identifier

Test id: `/req/jpeg2000-coverage/service-extension-identifier`

Test Purpose: `/req/jpeg2000-coverage/service-extension-identifier:`
 A WCS implementing this extension **shall** include the following URI in a `ows:Profile` element of the `ows:ServiceIdentification` in a *GetCapabilities* response:
http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpeg2000-access.

Test method: Send a *GetCapabilities* request to the server under test and verify that the response contains a `Profile` element with said URI.

Test passes if constraint evaluates to true.

A.1.4 Include format supported

Test id: `/req/jpeg2000-coverage/format-supported`

Test Purpose: `/req/jpeg2000-coverage/format-supported:`
A WCS implementing this extension **shall** include the following MIME type identifier in a `wcs:formatSupported` element in the `wcs:ServiceMetadata` element in a *GetCapabilities* response:
image/jp2 and/or image/jpx
according to compliance to ISO 15444-1 or ISO 15444-2
Dependency: http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpeg2000-coverage

Test method: Send a *GetCapabilities* request to the server under test and verify that the response contains a `wcs:formatSupported` element in the `wcs:ServiceMetadata` element with the value "*image/jp2*" and/or "*image/jpx*".

Test passes if constraint evaluates to true.

A.1.5 Native format

Test id: `/req/jpeg2000-coverage/native-format`

Test Purpose: `/req/jpeg2000-coverage/native-format:`
A coverage served via WCS and native format JPEG2000 **shall** use the following MIME type identifier in the `wcs:nativeFormat` element in the `wcs:ServiceParameters` element in a *DescribeCoverage* response:
image/jp2 or image/jpx
according to compliance of JPEG2000 files available on the server to ISO 15444-1 or ISO 15444-2
Dependency: http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpeg2000-coverage

Test method: Send *DescribeCoverage* requests to the server under test for each coverage known to have JPEG2000 as native format and verify that the responses contain a `wcs:nativeFormat` element in the `wcs:ServiceParameters` element with the value "*image/jp2*" or "*image/jpx*".

Test passes if constraint evaluates to true.

A.1.6 Format parameter

Test id: `/req/jpeg2000-coverage/format-requested`

Test Purpose: `/req/jpeg2000-coverage/format-requested:`
In a *GetCoverage* request requesting a coverage in JPEG2000 encoding the `format` parameter value **shall** be the following MIME type identifier:

`image/jp2` or `image/jpx`

Dependency: http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpeg2000-coverage

Test method: Send *GetCoverage* requests to the server under test for each coverage known to be able to be encoded in JPEG2000 (which are at least the ones known to have JPEG2000 as native format) with the `format` parameter set to "`image/jp2`" or "`image/jpx`" and verify that the responses are properly encoded in JPEG2000.

Test passes if constraint evaluates to true.

A.1.7 Additional parameters

Test id: `/req/jpeg2000-coverage/additional-parameters`

Test Purpose: `/req/jpeg2000-coverage/additional-parameters:`
The structure of a *GetCoverage* request requesting a coverage in JPEG2000 encoding **shall** be extended as defined in Table 2 and the respective XML Schema being part of this standard.

Test method: Send *GetCoverage* requests to the server under test for a coverage known to be available using JPEG2000 encoding for each parameter defined in Table 2 and each possible value for String and Boolean parameters and at least 3 different values for Integer parameters. Each request shall include one optional parameter respecting dependencies (e.g. `tileheight` needs `tiling` set to true).

Test passes if for each request the response either indicates (by inspection) that the parameter has been recognized and executed properly or is a valid exception as defined in **Error! Reference source not found.**

A.1.8 Format returned

Test id: `/req/jpeg2000-coverage/format-returned`

Test Purpose: `/req/jpeg2000-coverage/format-returned:`
The response to a successful *GetCoverage* request containing a `format` parameter with value `image/jp2` or `image/jpx` **shall**

consist of a coverage encoded as specified in the *OGC® GML Application Schema - Coverages – JPEG2000 Coverage Encoding Extension* [OGC 12-108].

Dependency: http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpeg2000-coverage

Test method: Send *GetCoverage* requests to the server under test for each coverage known to be able to be encoded in JPEG2000 (which are at least the ones known to have JPEG2000 as native format) with the `format` parameter set to "image/jp2" or "image/jpx" and verify that the responses are properly encoded in JPEG2000. Exercise tests for at least each of the following situations:

- `mediaType` parameter present with value "multipart/related"
 - No subsetting parameter
 - Trimming in one dimension
 - Trimming in two dimensions
- `mediaType` parameter not present

Test passes if for each request the response indicates (by inspection) that the parameter(s) has(have) been recognized and executed properly.

A.1.9 Parameter for profile

Test id: `/req/jpeg2000-coverage/profile`

Test Purpose: `/req/jeg2000-coverage/profile:`
The response to a successful *GetCoverage* request containing a `profile` parameter **shall** consist of a JPEG2000 encoded coverage according to JPEG2000 format Specifications ([3] and [4]).

Test method: Send *GetCoverage* requests to the server under test for each coverage known to be able to be encoded in JPEG2000 (which are at least the ones known to have JPEG2000 as native format) with the `format` parameter set to "image/jp2" or "image/jpx" and the "profile" parameter with all allowed values and verify that the responses are properly encoded in JPEG2000.

Test passes if for each request the response either indicates (by inspection) that the parameters have been recognized and executed properly or is the valid exception "ProfileNotSupported" as defined in Table 3.

A.1.10 Parameter for compression

Test id: /req/jpeg2000-coverage/compression

Test Purpose: /req/jpeg2000-coverage/compression:
The response to a successful *GetCoverage* request containing a compression parameter shall consist of a JPEG2000 encoded coverage using the specified compression rates.

Test method: Send *GetCoverage* requests to the server under test for each coverage known to be able to be encoded in JPEG2000 (which are at least the ones known to have JPEG2000 as native format) with the `format` parameter set to "*image/jp2*" or "*image/jpx*" and the "compression" parameter present for followings values of the "compression" parameter ("-", "10", "20", "50", "-,10,20,50") and verify that the responses are properly encoded in JPEG2000.

Test passes if for each request the response either indicates (by inspection) that the parameters have been recognized and executed properly or is the valid exception "CompressionNotSupported" as defined in Table 3.

A.1.11 Parameter for tiling

Test id: /req/jpeg2000-coverage/tiling

Test Purpose: /req/jpeg2000-coverage/tiling:
The response to a successful *GetCoverage* request containing a `tiling` and a `tileheight` and a `tilewidth` parameter **shall** consist of a JPEG2000 encoded coverage with internal tiling using the specified height and width.

Test method: Send *GetCoverage* requests to the server under test for each coverage known to be able to be encoded in JPEG2000 (which are at least the ones known to have JPEG2000 as native format) with the `format` parameter set to "*image/jp2*" or "*image/jpx*", the "tiling" parameter set to "true", and the "tileheight" and "tilewidth" parameters set to at least 3 different valid values and verify that the responses are properly encoded in JPEG2000.

Test passes if for each request the response either indicates (by inspection) that the parameters have been recognized and executed properly or is the valid exception "TilingNotSupported" as defined in Table 3.

A.1.12 Parameter for georeference

Test id: /req/jpeg2000-coverage/georeference

Test Purpose: /req/jpeg2000-coverage/georeference:
The response to a successful *GetCoverage* request containing a `georeference` parameter **shall** consist of a JPEG2000 encoded coverage with georeference information included.

Test method: Send *GetCoverage* requests to the server under test for each coverage known to be able to be encoded in JPEG2000 (which are at least the ones known to have JPEG2000 as native format) with the `format` parameter set to "*image/jp2*" or "*image/jpx*", the "`georeference`" parameter set to all possible values and verify that the responses are properly encoded in JPEG2000/GMLJP2.

Test passes if for each request the response either indicates (by inspection) that the parameters have been recognized and executed properly or is the valid exception " `GeoreferenceNotSupported`" as defined in Table 3.

A.1.13 Exceptions

Test id: /req/jpeg2000-coverage/exceptions

Test Purpose: /req/jpeg2000-coverage/exceptions:
When a WCS server encounters an error described in column "meaning of exception code" in Table 3 then it **shall** return the corresponding exception report message with the contents of the locator parameter value as specified in the right column of Table 3.
Dependency: <http://www.opengis.net/spec/WCS/2.0/conf/core>

Test method: Send *GetCoverage* requests to the server under test for a coverage known to be available using JPEG2000 encoding for each parameter defined in Table 2 including exactly one optional and using an invalid value.

Test passes if for each request the response is a valid exception as defined in Table 3 using the relevant `exceptionCode`.

A.2 Conformance Test Class: *jpip-access*

The OGC URI identifier of this conformance class is:

http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpip-access.

A.2.1 Prerequisites

Make sure that at least one coverage with JPEG2000 as native format is available from server under test.

A.2.2 Include GMLCOV extension identifier

Test id: `/req/jpip-access/gmlcov-extension-identifier`

Test Purpose: `/req/jpip-access/gmlcov-extension-identifier:`
A WCS implementing this extension **shall** include the following URI in a `ows:Profile` element of the `ows:ServiceIdentification` in a *GetCapabilities* response:
http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpeg2000-coverage.
Dependency: http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpeg2000-coverage

Test method: Send a *GetCapabilities* request to the server under test and verify that the response contains a `Profile` element with said URI.

Test passes if constraint evaluates to true.

A.2.3 Include Service extension identifier

Test id: `/req/jpip-access/service-extension-identifier`

Test Purpose: `/req/jpip-access/service-extension-identifier:`
A WCS implementing this extension **shall** include the following URI in a `ows:Profile` element of the `ows:ServiceIdentification` in a *GetCapabilities* response:
http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpip-access.

Test method: Send a *GetCapabilities* request to the server under test and verify that the response contains a `Profile` element with said URI.

Test passes if constraint evaluates to true.

A.2.4 Include format supported

Test id: `/req/jpeg2000-coverage/format-supported`

Test Purpose: `/req/jpeg2000-coverage/format-supported:`
A WCS implementing this extension **shall** include the following MIME type identifier in a `wcs:formatSupported` element in the `wcs:ServiceMetadata` element in a *GetCapabilities* response:
image/jp2 and/or image/jpx
according to compliance to ISO 15444-1 or ISO 15444-2

Dependency: http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpeg2000-coverage

Test method: Send a *GetCapabilities* request to the server under test and verify that the response contains a `wcs:formatSupported` element in the `wcs:ServiceMetadata` element with the value "*image/jp2*" and/or "*image/jpx*".

Test passes if constraint evaluates to true.

A.2.5 Native format

Test id: `/req/jpeg2000-coverage/native-format`

Test Purpose: `/req/jpeg2000-coverage/native-format:`
A coverage served via WCS and native format JPEG2000 **shall** use the following MIME type identifier in the `wcs:nativeFormat` element in the `wcs:ServiceParameters` element in a *DescribeCoverage* response:

`image/jp2` or `image/jpx`

according to compliance of JPEG2000 files available on the server to ISO 15444-1 or ISO 15444-2

Dependency: http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpeg2000-coverage

Test method: Send *DescribeCoverage* requests to the server under test for each coverage known to have JPEG2000 as native format and verify that the responses contain a `wcs:nativeFormat` element in the `wcs:ServiceParameters` element with the value "*image/jp2*" or "*image/jpx*".

Test passes if constraint evaluates to true.

A.2.6 Format parameter

Test id: `/req/jpeg2000-coverage/format-requested`

Test Purpose: `/req/jpeg2000-coverage/format-requested:`
In a *GetCoverage* request requesting a coverage in JPEG2000 encoding the `format` parameter value **shall** be the following MIME type identifier:

`image/jp2` or `image/jpx`

Dependency: http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpeg2000-coverage

Test method: Send *GetCoverage* requests to the server under test for each coverage known to be able to be encoded in JPEG2000 (which are at least the

ones known to have JPEG2000 as native format) with the `format` parameter set to "image/jp2" or "image/jpx" and verify that the responses are properly encoded in JPEG2000.

Test passes if constraint evaluates to true.

A.2.7 Additional parameters

Test id: `/req/jpeg2000-coverage/additional-parameters`

Test Purpose: `/req/jpeg2000-coverage/additional-parameters:`
The structure of a *GetCoverage* request requesting a coverage in JPEG2000 encoding **shall** be extended as defined in Table 2 and the respective XML Schema being part of this standard.

Test method: Send *GetCoverage* requests to the server under test for a coverage known to be available using JPEG2000 encoding for each parameter defined in Table 2 and each possible value for String and Boolean parameters and at least 3 different values for Integer parameters. Each request shall include one optional parameter respecting dependencies (e.g. `tileheight` needs `tiling` set to true).

Test passes if for each request the response either indicates (by inspection) that the parameter has been recognized and executed properly or is a valid exception as defined in Table 3.

A.2.8 Format returned

Test id: `/req/jpeg2000-coverage/format-returned`

Test Purpose: `/req/jpeg2000-coverage/format-returned:`
The response to a successful *GetCoverage* request containing a `format` parameter with value `image/jp2` or `image/jpx` **shall** consist of a coverage encoded as specified in the *OGC® GML Application Schema - Coverages – JPEG2000 Coverage Encoding Extension* [OGC 12-108].
Dependency: http://www.opengis.net/spec/GMLCOV_jpeg2000-coverages/1.0/conf/jpeg2000-coverage

Test method: Send *GetCoverage* requests to the server under test for each coverage known to be able to be encoded in JPEG2000 (which are at least the ones known to have JPEG200 as native format) with the `format` parameter set to "image/jp2" or "image/jpx" and verify that the responses are properly encoded in JPEG2000. Exercise tests for at least each of the following situations:

- `mediaType` parameter present with value

"multipart/related"

- No subsetting parameter
- Trimming in one dimension
- Trimming in two dimensions
- mediaType parameter not present

Test passes if for each request the response indicates (by inspection) that the parameter(s) has(have) been recognized and executed properly.

A.2.9 Parameter for profile

Test id: /req/jpeg2000-coverage/profile

Test Purpose: /req/jeg2000-coverage/profile:
The response to a successful *GetCoverage* request containing a `profile` parameter **shall** consist of a JPEG2000 encoded coverage according to JPEG2000 format Specifications ([3] and [4]).

Test method: Send *GetCoverage* requests to the server under test for each coverage known to be able to be encoded in JPEG2000 (which are at least the ones known to have JPEG2000 as native format) with the `format` parameter set to "*image/jp2*" or "*image/jpx*" and the "`profile`" parameter with all allowed values and verify that the responses are properly encoded in JPEG2000.

Test passes if for each request the response either indicates (by inspection) that the parameters have been recognized and executed properly or is the valid exception "`ProfileNotSupported`" as defined in Table 3.

A.2.10 Parameter for compression

Test id: /req/jpeg2000-coverage/compression

Test Purpose: /req/jpeg2000-coverage/compression:
The response to a successful *GetCoverage* request containing a `compression` parameter shall consist of a JPEG2000 encoded coverage using the specified compression rates.

Test method: Send *GetCoverage* requests to the server under test for each coverage known to be able to be encoded in JPEG2000 (which are at least the ones known to have JPEG2000 as native format) with the `format` parameter set to "*image/jp2*" or "*image/jpx*" and the "`compression`" parameter present for followings values of the "`compression`" parameter ("`-`", "`10`", "`20`", "`50`", "`-,10,20,50`") and verify that the

responses are properly encoded in JPEG2000.

Test passes if for each request the response either indicates (by inspection) that the parameters have been recognized and executed properly or is the valid exception "CompressionNotSupported" as defined in Table 3.

A.2.11 Parameter for tiling

Test id: /req/jpeg2000-coverage/tiling

Test Purpose: /req/jpeg2000-coverage/tiling:
The response to a successful *GetCoverage* request containing a *tiling* and a *tileheight* and a *tilewidth* parameter **shall** consist of a JPEG2000 encoded coverage with internal tiling using the specified height and width.

Test method: Send *GetCoverage* requests to the server under test for each coverage known to be able to be encoded in JPEG2000 (which are at least the ones known to have JPEG2000 as native format) with the *format* parameter set to "image/jp2" or "image/jpx", the "tiling" parameter set to "true", and the "tileheight" and "tilewidth" parameters set to at least 3 different valid values and verify that the responses are properly encoded in JPEG2000.

Test passes if for each request the response either indicates (by inspection) that the parameters have been recognized and executed properly or is the valid exception "TilingNotSupported" as defined in Table 3.

A.2.12 Parameter for georeference

Test id: /req/jpeg2000-coverage/georeference

Test Purpose: /req/jpeg2000-coverage/georeference:
The response to a successful *GetCoverage* request containing a *georeference* parameter **shall** consist of a JPEG2000 encoded coverage with georeference information included.

Test method: Send *GetCoverage* requests to the server under test for each coverage known to be able to be encoded in JPEG2000 (which are at least the ones known to have JPEG2000 as native format) with the *format* parameter set to "image/jp2" or "image/jpx", the "georeference" parameter set to all possible values and verify that the responses are properly encoded in JPEG2000/GMLJP2.

Test passes if for each request the response either indicates (by inspection) that the parameters have been recognized and executed

properly or is the valid exception " GeoreferenceNotSupported" as defined in Table 3.

A.2.13 Exceptions

Test id: /req/jpeg2000-coverage/exceptions

Test Purpose: /req/jpeg2000-coverage/exceptions:
When a WCS server encounters an error described in column “meaning of exception code” in Table 3 then it **shall** return the corresponding exception report message with the contents of the locator parameter value as specified in the right column of Table 3.
Dependency: <http://www.opengis.net/spec/WCS/2.0/conf/core>

Test method: Send *GetCoverage* requests to the server under test for a coverage known to be available using JPEG2000 encoding for each parameter defined in Table 2 including exactly one optional and using an invalid value.

Test passes if for each request the response is a valid exception as defined in Table 3 using the relevant exceptionCode.

-- end of ATS --

Annex B: Revision history

Date	Release	Editor	Primary clauses modified	Description
2014-06-23	0.0.1	Dimitri Sarafinof	All	First draft based on discussions in the WCS.SWG.
2014-10-22	0.1.0	Dimitri Sarafinof	All	Feedback from OGC (Calgary TC) and DGIWG (Madrid TP)
2014-11-12	0.2.0	Dimitri Sarafinof	All	OGC document number and cleaning for pending document
2015-04-08	0.3.0	Dimitri Sarafinof	All	Alignment with OGC 12-108, examples added
2016-05-25	1.0	Scott Simmons	All	Prepare for publication