

# Open Geospatial Consortium

Submission Date: 2015-08-10

Approval Date: 2016-05-11

Publication Date: 2016-12-22

External identifier of this OGC® document: <http://www.opengis.net/doc/dp/wqs/>

Internal reference number of this Document: OGC 14-121r2

Category: OGC® Discussion Paper

Editor: Peter Baumann

## OGC® Web Query Service

### Copyright notice

Copyright © 2016 Open Geospatial Consortium.

To obtain additional rights of use, visit <http://www.opengeospatial.org/legal/>.

### Warning

This document is not an OGC Standard. This is an OGC Discussion Paper and is therefore not an official position of the OGC membership. The document is distributed for review and comment. It is subject to change without notice and may not be referred to as an OGC Standard. Further, an OGC Discussion Paper should not be referenced as required or mandatory technology in procurements.

Document type: OGC® Discussion Paper

Document subtype:

Document stage: Approved

Document language: English

## OGC 14-121r2

### License Agreement

Permission is hereby granted by the Open Geospatial Consortium, ("Licensor"), free of charge and subject to the terms set forth below, to any person obtaining a copy of this Intellectual Property and any associated documentation, to deal in the Intellectual Property without restriction (except as set forth below), including without limitation the rights to implement, use, copy, modify, merge, publish, distribute, and/or sublicense copies of the Intellectual Property, and to permit persons to whom the Intellectual Property is furnished to do so, provided that all copyright notices on the intellectual property are retained intact and that each person to whom the Intellectual Property is furnished agrees to the terms of this Agreement.

If you modify the Intellectual Property, all copies of the modified Intellectual Property must include, in addition to the above copyright notice, a notice that the Intellectual Property includes modifications that have not been approved or adopted by LICENSOR.

THIS LICENSE IS A COPYRIGHT LICENSE ONLY, AND DOES NOT CONVEY ANY RIGHTS UNDER ANY PATENTS THAT MAY BE IN FORCE ANYWHERE IN THE WORLD.

THE INTELLECTUAL PROPERTY IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND NON-INFRINGEMENT OF THIRD PARTY RIGHTS. THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS NOTICE DO NOT WARRANT THAT THE FUNCTIONS CONTAINED IN THE INTELLECTUAL PROPERTY WILL MEET YOUR REQUIREMENTS OR THAT THE OPERATION OF THE INTELLECTUAL PROPERTY WILL BE UNINTERRUPTED OR ERROR FREE. ANY USE OF THE INTELLECTUAL PROPERTY SHALL BE MADE ENTIRELY AT THE USER'S OWN RISK. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR ANY CONTRIBUTOR OF INTELLECTUAL PROPERTY RIGHTS TO THE INTELLECTUAL PROPERTY BE LIABLE FOR ANY CLAIM, OR ANY DIRECT, SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM ANY ALLEGED INFRINGEMENT OR ANY LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR UNDER ANY OTHER LEGAL THEORY, ARISING OUT OF OR IN CONNECTION WITH THE IMPLEMENTATION, USE, COMMERCIALIZATION OR PERFORMANCE OF THIS INTELLECTUAL PROPERTY.

This license is effective until terminated. You may terminate it at any time by destroying the Intellectual Property together with all copies in any form. The license will also terminate if you fail to comply with any term or condition of this Agreement. Except as provided in the following sentence, no such termination of this license shall require the termination of any third party end-user sublicense to the Intellectual Property which is in force as of the date of notice of such termination. In addition, should the Intellectual Property, or the operation of the Intellectual Property, infringe, or in LICENSOR's sole opinion be likely to infringe, any patent, copyright, trademark or other right of a third party, you agree that LICENSOR, in its sole discretion, may terminate this license without any compensation or liability to you, your licensees or any other party. You agree upon termination of any kind to destroy or cause to be destroyed the Intellectual Property together with all copies in any form, whether held by you or by any third party.

Except as contained in this notice, the name of LICENSOR or of any other holder of a copyright in all or part of the Intellectual Property shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Intellectual Property without prior written authorization of LICENSOR or such copyright holder. LICENSOR is and shall at all times be the sole entity that may authorize you or any third party to use certification marks, trademarks or other special designations to indicate compliance with any LICENSOR standards or specifications. This Agreement is governed by the laws of the Commonwealth of Massachusetts. The application to this Agreement of the United Nations Convention on Contracts for the International Sale of Goods is hereby expressly excluded. In the event any provision of this Agreement shall be deemed unenforceable, void or invalid, such provision shall be modified so as to make it valid and enforceable, and as so modified the entire Agreement shall remain in full force and effect. No decision, action or inaction by LICENSOR shall be construed to be a waiver of any rights or remedies available to it.

<b>Contents</b>	<b>Page</b>
1 Scope.....	4
2 Conformance.....	4
3 Terms and definitions.....	4
4 Class <i>Query</i> .....	4
Annex A Abstract test suite .....	9
Annex B (non-normative) Examples .....	11
Annex C (normative) Schema.....	14
Bibliography.....	15



<b>Tables</b>	<b>Page</b>
Table 1 — Components of WQS : : Query request structure .....	5
Table 2 — <i>Query</i> exception codes.....	7

## i. Abstract

This OGC *Web Query Service* (WQS) defines a service interface for retrieving any kind of subset of information provided by the server addressed. WQS is completely agnostic of any semantics and, therefore, not bound to any predefined structures, such as coordinates, features, coverages, or metadata. This makes WQS particularly suitable for retrieval from heterogeneous data offerings combining features, coverages, and catalog information in some application-defined way. A second use case is selective retrieval from a Capabilities document to avoid downloading large such documents and performing extraction on client side.

To this end, the *Query* request type is defined which, based on an XPath expression as input, extracts the matching information from the service's offering and returns it (currently: as an XML document).

## ii. Keywords

ogcdoc, Web Query Service, query, xpath

## iii. Preface

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. The Open Geospatial Consortium shall not be held responsible for identifying any or all such patent rights.

Recipients of this document are requested to submit, with their comments, notification of any relevant patent claims or other intellectual property rights of which they may be aware that might be infringed by any implementation of the standard set forth in this document, and to provide supporting documentation.

## iv. Submitters

The following organizations have submitted this Interface Specification to the Open Geospatial Consortium, Inc.:

- Jacobs University Bremen

## v. Document Contributor Contact Points

Name	Organization
Peter Baumann	Jacobs University Bremen, rasdaman GmbH

## vi. Revision history

Date	Release	Author	Paragraph modified	Description
2014-12-01	0.0.1	Peter Baumann	All	Created
2016-04-05	1.0.0	Peter Baumann	Several	Reformatted for publication

## vii. Future Work

Extensions to this concept might address the following aspects:

- Extending model capabilities from hierarchical structures (as supported now) to more general structures (such as semantic graphs);
- Extending query capabilities from XPath to further, more powerful paradigms (such as SPARQL);
- Adding further encodings, such as JSON; and
- Adopting this functionality as part of OWS Common, given its general, overarching relevance.

## 1 Scope

This OGC Web Query Service (WQS) specification defines how to selectively retrieve data from a server, without making any assumption about the data offered.

## 2 Conformance

This document establishes the following requirements and conformance classes:

- *query*, of URI <http://www.opengis.net/spec/WQS/1.0/req/xpath>; the corresponding conformance class is *xpath*, with URI <http://www.opengis.net/spec/WQS/1.0/conf/xpath>.

This is the mandatory conformance class of this specification.

Standardisation target are WQS implementations (currently: servers).

Requirements URIs defined in this document are given by

<http://www.opengis.net/spec/WQS/1.0/req/req{reqname}>,

conformance test URIs are given by

<http://www.opengis.net/spec/WQS/1.0/conf/req{reqname}>.

whereby {reqname} in the numbering scheme is to be substituted by the requirement identifier provided in the text.

Annex A of this document lists the conformance tests which shall be exercised on any software artefact claiming to implement WQS.

## 3 Terms and definitions

For the purposes of this document, the terms and definitions given in the above references apply. In addition, the following terms and definitions apply. An arrow “□” indicates that the following term is defined in this Clause.

### 3.1

#### **Offering [of a service]**

The complete information which a service provides for retrieval by clients, conceptually represented by a single XML document.

## 4 Class *Query*

### 4.1 Overview

This Clause 4 defines the mandatory core requirements class, *query*. Clients and servers supporting this *query* requirements class shall support XPath-based selection from a WQS server's coverage offerings through a dedicated request type, *Query*, operating on the information offering of the WQS service, seen as a single XML document.



## 4.2 *GetCapabilities* request

A server announces support of the *query* requirements class to a client by adding the URL identifying this extension to the list of supported extensions delivered in the Capabilities document.

### Requirement 1 – profile:

A WQS service implementing requirements class *query* **shall** include the following URI in the Profile element of the ServiceIdentification in a *GetCapabilities* response: <http://www.opengis.net/spec/WQS/1.0/conf/query>

## 4.3 *Query* request

### 4.3.1 *Query* request

This request assumes an XML document on the server which is of some structure not specified further; in particular, no specific underlying schema is assumed. Part of this offering may be the Capabilities document, but this is at the discretion of the service.

The XPath expression submitted is evaluated against this single conceptual XML document, and the result is returned to the client.

### Requirement 2 – request:

A *Query* request **shall** adhere to Figure 1 and Table 1.




Figure 1 — *Query* request UML diagram

Table 1 — Components of WQS : :*Query* request structure

Name	Definition	Data type	Multiplicity
query	XPath expression to be evaluated by the server	string	one (mandatory)
Format	Identifier of the output format, expressed as MIME type	string	Zero or one (optional)

**Requirement 3 - xpath:**

The `query` parameter in a *Query* request **shall** contain a syntactically valid XPath expression as per W3C XPath [1].

Example The following examples are valid expressions which may yield nonempty results on a Capabilities document; specifically, it extracts all data formats supported by this server:

```
//formatSupported
```

### 4.3.2 Query response

The response to a successful *Query* request is a document (which may contain XML tags) containing the information extracted from the server's offering in some appropriate encoding.

**Requirement 4 – response:**

The response to a successful *Query* request **shall** be given by the evaluation of the `query` argument against the offering of the WQS server.

Note: A server may reject requests generating foreseeably excessive amounts of data, such as retrieving an image encoded in GML.

**Requirement 5 – encoding:**

The response to a successful *Query* request containing a `format` parameter **shall** be encoded in the format specified by the `format` parameter.

Note 1: If no format parameter is provided in a request then the server may choose some default encoding on its own.

Note 2: Container formats like GMLJP2, zip, etc. are particularly amenable to heterogeneous information retrieval.

## 4.4 Request Encodings

### 4.4.1 Overview

This Subclause specifies the encoding of a *Query* operation for each WQS protocol binding that a client and server support.

### 4.4.2 GET/KVP Encoding

**Requirement 6 – get-kvp:**

In a *Query* request using the GET/KVP protocol, a `query` parameter with value `x` **shall** be represented by an http key/value pair as follows, with `x` properly using http entities where required:

```
QUERY=x
```

Example The following is a complete *Query* request in GET/KVP notation; it delivers a list of all coverage identifiers:

```
http://www.acme.com/ows?  
SERVICE=WQS &  
VERSION=1.0 &
```

```
REQUEST= Query &
QUERY=/Capabilities/Contents/CoverageSummary/CoverageId &
FORMAT=application/gml+xml
```

#### 4.4.3 XML/POST Encoding

##### Requirement 7 – xml-post:

A *Query* request using the XML/POST protocol **shall** be encoded as an `wis:query` element as defined in the XML Schema accompanying this specification.

Example The following is a complete *Query* request plus a response (assuming success) in XML/POST encoding:

```
<?xml version="1.0" encoding="UTF-8"?>
<wis:query xmlns:wis="http://www.opengis.net/wis/1.0">
  <wis:query>
    /Capabilities/Contents/CoverageSummary/CoverageId
  </wis:query>
</wis:Query>
```

#### 4.4.4 SOAP Encoding

##### Requirement 8 – soap:

A *Query* request using the SOAP protocol **shall** be encoded as a `wis:query` element as defined in the XML Schema accompanying this specification.

#### 4.5 Exceptions

##### Requirement 9 – exceptions:

When a WQS server encounters an error while evaluating a *Query* operation the server **shall** return an exception report message from the list in Table 2 with a `locator` parameter value as specified in the right column of Table 2 for each `exceptionCode` listed.

Table 2 — *Query* exception codes

exceptionCode value	HTTP code	Meaning of exception code	locator value
InvalidQuery	404	QUERY parameter does not represent a valid XPath expression	Position of violating element / parameter
InvalidFormat	404	FORMAT parameter does not specify a known MIME type, or result cannot be encoded in the format requested	FORMAT parameter
NoMatch	404	XPath expression in QUERY parameter does not address any element defined in the server offering	Position of violating element / parameter

**OGC 14-121r2**

ExcessiveResultVolume	404	Query would return an excessive amount of data (e.g., when requesting coverage range sets)	n.a.
-----------------------	-----	--	------

## Annex A

### Abstract test suite

A WQS implementation must satisfy the following system characteristics to be conformant with this specification.

Test identifiers are relative to <http://www.opengis.net/spec/WQS/1.0/query/conf>. The identifier of each test consists of this path, a “/” (slash) character, and the name of the corresponding requirement.

#### A.1 Conformance Test Class: *query*

The OGC URI identifier of this conformance class is:  
<http://www.opengis.net/spec/WQS/1.0/conf/query>.

<b>Test Purpose:</b>	Requirement 1
<b>Test method:</b>	Send valid <i>GetCapabilities</i> request to system under test. Check Capabilities document returned whether it contains the required element in the proper position.  Test passes if all conditions are fulfilled.

<b>Test Purpose:</b>	Requirement 2
<b>Test method:</b>	Send <i>Query</i> requests to system under test. Verify that the structures referenced by the requirement are accepted by the server (and returned in responses, respectively), and only those. To this end, send both valid and violating requests; in case of automatically verifiable definitions (such as XML Schema), verify through appropriate tools; otherwise (such as with UML), implement according tests manually. Test passes if all conditions are fulfilled.

<b>Test Purpose:</b>	Requirement 3
<b>Test method:</b>	Send <i>Query</i> requests to system under test containing correct and incorrect XPath expressions in the <code>query</code> parameter. Check responses to contain an exception exactly for the incorrect parameters.  Test passes if all conditions are fulfilled.

<b>Test Purpose:</b>	Requirement 4
<b>Test method:</b>	Send valid <i>Query</i> requests to system under test. Check that request was successful and returned the appropriate result.

Test passes if all conditions are fulfilled.

**Test Purpose:** Requirement 5

**Test method:** Send valid *Query* requests to system under test containing a format parameter with a valid MIME type identifying a format that allows representing the result. Check that the response is encoded in the format requested.

Test passes if all conditions are fulfilled.

**Test Purpose:** Requirement 6

**Test method:** Send a valid *Query* request using the GET/KVP protocol to system under test following this encoding specification. Check that request was successful.

Test passes if all conditions are fulfilled.

**Test Purpose:** Requirement 7

**Test method:** Send a valid *Query* request using the POST/XML protocol to system under test following this encoding specification. Check that request was successful.

Test passes if all conditions are fulfilled.

**Test Purpose:** Requirement 8

**Test method:** Send a valid *Query* request using the SOAP protocol to system under test following this encoding specification. Check that request was successful.

Test passes if all conditions are fulfilled.

**Test Purpose:** Requirement 9

**Test method:** For each exception situation defined, send an invalid *Query* request resembling such a situations. Check that the appropriate exception is returned.


Test passes if all conditions are fulfilled.

-- end of ATS --

**Annex B  
(non-normative)**

**Examples**

This Annex contains examples of *Query* requests and responses assuming the conceptual model of a Web Coverage Service (WCS) [2], see Figure 2. Note that the actual responses depend on the server’s concrete, individual offerings and will normally be at least in part be different from the results displayed.



**Figure 2 — WCS service offering UML diagram, based on OGC WCS [2]**

- “The complete Capabilities document”

XPath request:

```
/CoverageOfferings/Capabilities
```

Response: a standard Capabilities document.

- “All WCS Extensions supported by this server”

XPath request:

```
/CoverageOffering/Capabilities/ServiceIdentification/Profile/text()
```

Shorthand version: //Profile/text()

Sample response:

```
http://www.opengis.net/spec/GMLCOV/1.0/conf/gml
http://www.opengis.net/spec/GMLCOV/1.0/conf/gml-coverage
http://www.opengis.net/spec/GMLJP2/2.0
http://www.opengis.net/spec/WCS_coverage-encoding_geotiff/1.0
```

## OGC 14-121r2

```
http://www.opengis.net/spec/WCS_coverage-encoding_jpeg2000/1.0/  
http://www.opengis.net/spec/WCS_coverage-encoding_netcdf/1.0  
http://www.opengis.net/spec/WCS_protocol-binding_get-kvp/1.0/conf/get-kvp  
http://www.opengis.net/spec/WCS_protocol-binding_post-xml/1.0  
http://www.opengis.net/spec/WCS_protocol-binding_soap/1.0  
http://www.opengis.net/spec/WCS_protocol-binding_get-rest/1.0/conf/get-rest  
http://www.opengis.net/spec/WCS_service-  
extension_processing/2.0/conf/processing  
http://www.opengis.net/spec/WCS_service-extension_range-  
subsetting/1.0/conf/record-subsetting  
http://www.opengis.net/spec/WCS_service-  
extension_transaction/2.0/conf/insert+delete  
http://www.opengis.net/spec/WCS_service-extension_scaling/1.0/conf/scaling  
http://www.opengis.net/spec/WCS_service-  
extension_interpolation/1.0/conf/interpolation  
http://www.opengis.net/spec/WCPS/1.0/conf/wcps-core
```

- “All data formats supported by this server”

### XPath request:

```
/CoverageOfferings/Capabilities/ServiceIdentification/ServiceMeta  
data/formatSupported/text ()
```

Shorthand version: //formatSupported/text ()

### Sample response:

```
application/netcdf  
image/jp2  
image/tiff  
image/png  
application/gml+xml
```

- “Identifiers of all coverages offered”

### XPath request:

```
/CoverageOffering/Capabilities/Contents/CoverageSummary/CoverageId/text ()
```

Shorthand version: //CoverageId/text ()

### Sample response:

```
NASA_NIGHT_EARTH  
NASA_NIGHT_EARTH_SCALED_SHALLOW_TOPO
```

- “spatial extent of coverage X”

### XPath request:

```
//coverage[@id="X"]/boundedBy
```

### Sample response:



```

<boundedBy>
  <Envelope
    srsName="http://www.opengis.net/def/crs/EPSG/0/4326"
    axisLabels="Lat Long"
    uomLabels="deg deg"
    srsDimension="2">
    <lowerCorner>-79 -0.01</lowerCorner>
    <upperCorner>0 59</upperCorner>
  </Envelope>
</boundedBy>

```

- “spatio-temporal locations of all 3-D coverages on this server”.

XPath request:

```
//coverage/[@srsDimension=3]/boundedBy
```

Sample response:

(sequence of GML boundedBy elements)

- “Native CRS of coverage X”

XPath request:

```
//coverage[@id="X"]/boundedBy/Envelope/@srsName
```

Sample response:

```
http://www.opengis.net/def/crs/EPSG/0/4326
```

- “Pixel values of coverage X”

This is likely **not** supported to avoid returning excessively large documents.

For retrieval of coverages in GML use a GetCoverage request with

```
FORMAT=application/gml+xml
```

(if supported by the server, which can be checked in the in the Profile section of the Capabilities document).

## Annex C (normative)

### Schema

The following is the wqs.xsd file:

```
<?xml version="1.0" encoding="UTF-8"?>
<schema targetNamespace="http://www.opengis.net/wqs/1.0"
  xmlns:wqs="http://www.opengis.net/wqs/1.0"
  xmlns="http://www.w3.org/2001/XMLSchema"
  elementFormDefault="qualified"
  version="1.0.0">
  <annotation>
    <appinfo>wqs.xsd</appinfo>
    <documentation>OGC Web Query Service 1.0
    Last updated: 2016-aug-19
    Copyright (c) 2016 Open Geospatial Consortium. All Rights Reserved.
    To obtain additional rights of use, visit
    http://www.opengeospatial.org/legal/.
    </documentation>
  </annotation>
  <element name="query" type="wqs:QueryType">
    <annotation>
      <documentation>This is the representation of a WQS query re-
    quest.</documentation>
    </annotation>
  </element>
  <complexType name="QueryType">
    <sequence>
      <element name="query" type="string"/>
      <element name="format" type="string" minOccurs="0"/>
    </sequence>
    <attribute name="service" type="string" use="required" fixed="WQS"/>
    <attribute name="version" type="string" use="required"/>
  </complexType>
</schema>
```

## Bibliography

- [1] W3C: XML Path Language (XPath) Version 1.0. W3C Recommendation 16 November 1999, <http://www.w3.org/TR/xpath/> (1999)
- [2] OGC: [OGC 09-110r4] OGC Web Coverage Service (WCS) 2.0 – Core. Version 2.0.1 (2012)